


INLINE FILTERS FP

Used for households, industry, services...

- Heating system protection
- Sediment pretreatment for water treatment systems
- Prefilter for reverse osmosis systems
- Carbon filtration



FP SERIES: 5 , 7 , 9 3/4 , 20 .



□ Three or two-part inline filter

- Polypropylene head with brass inserts and decompress valve
- Clear SAN* or white PP* housing
- In/out 1 , 3 or 1
- Working pressure 8 bar
- Max. temp. 50°C
- Hygienic certificate PZH

*SAN – styrene – acrylic nitril resin
**PP – polypropylene

Accessories:

- Mounting bracket
- Wrench

FP	FP 5''			FP 7''			FP 9 3/4 ''			FP 20''		
In/out diameter [inch]	1/2	3/4	1	1/2	3/4	1	1/2	3/4	1	1/2	3/4	1
Nominal flow [m ³ /h]	1,2			2,5			3,5			7,0		
Diameter [A] x height [B] [mm]	122x186			122x236			122x308			122x566		

FILTER CARTRIDGES



SEDIMENT: stop sand, rust, oxidized iron, improve turbidity and color

Type	Symbol	Height		Filtration (micron)				
String cartridges	FA	5''	7''			5	20	
String cartridges	FA			9 3/4''		20	50 100	
String cartridges	FA				20''	1	5 10 20 50 100	
Polypropylene cartridges	FCP5	5''		9 3/4''	20''	1	5	20
Polypropylene cartridges	FR	5''	7''	9 3/4''	20''	1	5 20 50	
Net cartridges	RLA	5''	7''	9 3/4''	20''		80	

CARBON: absorb smell and improve taste of water (chlorine, organic substances)

Type	Symbol	Height		Filtration (micron)	
Carbon block	BL	5''		9 3/4''	20''
Granular carbon cartridges	FCCB	5''		9 3/4''	20''
Granular carbon cartridges	GAC	5''		9 3/4''	20''
String – carbon cartridges	FACA	5''	7''	9 3/4''	20''
Carbon cartridge (powdery)	RLACA	5''	7''	9 3/4''	
Fiber – carbon cartridge	FRC		7''	9 3/4''	20''

PROEKO WATER TREATMENT FOR HOME AND INDUSTRY

95-050 Konstanynow Lodzki , ul. Srebrzynska 5/7

tel: 42 211 20 64, 42 211 20 19 fax: 42 09 33 03

e-mail: proeko@proekojp.pl

www.proekojp.pl